

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 12/22/2015

LA-CO Industries, Inc.

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Temperature indicator

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Acute Tox. 4 (Oral) H302
Resp. Sens. 1 H334
Skin Sens. 1 H317
Muta. 2 H341
Carc. 1A H350
Repr. 1B H360
STOT RE 2 H373
Aquatic Acute 1 H400
Aquatic Chronic 1 H410

Full text of hazard classes and H-statements : see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

GHS08

GHS09

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H302 - Harmful if swallowed
H317 - May cause an allergic skin reaction
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341 - Suspected of causing genetic defects
H350 - May cause cancer
H360 - May damage fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H400 - Very toxic to aquatic life
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe dust
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P272 - Contaminated work clothing must not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear eye protection, protective clothing, protective gloves

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

P284 - In case of insufficient ventilation, wear suitable respiratory equipment
P301+P312 - If swallowed: Call a doctor if you feel unwell
P302+P352 - If on skin: Wash with plenty of water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P308+P313 - If exposed or concerned: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (see First aid measures on this label)
P330 - Rinse mouth
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P342+P311 - If experiencing respiratory symptoms: Call a doctor
P363 - Wash contaminated clothing before reuse
P391 - Collect spillage
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
cobalt sulphate	(CAS No) 10124-43-3	38.74 – 39.18 : 750 °F 40.52 – 40.97 : 800 °F	Acute Tox. 4 (Oral), H302 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 Repr. 1B, H360 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
nickel sulphate	(CAS No) 7786-81-4	< 0.35 : 750 °F < 0.45 : 800 °F	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Irrit. 2, H315 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1A, H350 Repr. 1B, H360 STOT RE 1, H372 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

First-aid measures after skin contact : If skin irritation or rash occurs: Get medical advice/attention. Wash with plenty of soap and water. Wash contaminated clothing before reuse.

First-aid measures after eye contact : In case of contact, immediately flush eyes with plenty of water. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a POISON CENTER or doctor/physician if you feel unwell. Rinse mouth.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : May cause cancer. Suspected of causing genetic defects. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause cancer by inhalation.

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Burning produces irritating, toxic and noxious fumes.
Explosion hazard : Product is not explosive.
Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

Firefighting instructions : Do not allow run-off from fire fighting to enter drains or water courses.
Protection during firefighting : Wear a self contained breathing apparatus. Wear fire/flame resistant/retardant clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Avoid contact with skin, eyes and clothing. Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Wear suitable gloves.
Emergency procedures : Ventilate area. Stop leak if safe to do so.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain and collect as any solid.
Methods for cleaning up : Minimize generation of dust.

6.4. Reference to other sections

Section 8: personal protective equipment. Section 7: safe handling.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin, eyes and clothing. Avoid breathing dust. Obtain special instructions before use. Use personal protective equipment as required. Do not handle until all safety precautions have been read and understood.
Hygiene measures : Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container closed when not in use.
Incompatible products : Strong acids. Strong bases. Strong oxidizers.
Heat and ignition sources : Keep away from heat, sparks and flame.
Prohibitions on mixed storage : Incompatible materials.
Storage area : Store in dry, cool, well-ventilated area.

7.3. Specific end use(s)

Temperature indicator.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

ACGIH	Not applicable
-------	----------------

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)		
OSHA	Not applicable	
cobalt sulphate (10124-43-3)		
ACGIH	ACGIH TWA (mg/m ³)	0.02 mg/m ³ Cobalt and inorganic compounds, as Co
ACGIH	Remark (ACGIH)	Notations A3, BEI. MW Varies.
OSHA	Not applicable	
nickel sulphate (7786-81-4)		
ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: Use rubber gloves.
Eye protection	: In case of dust production: protective goggles.
Skin and body protection	: Long sleeved protective clothing.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges. NIOSH. Approved respirator.
Other information	: Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Variable.
Odour	: No data available
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

Strong acids. Strong bases. Strong oxidizers.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)	
ATE CLP (oral)	1843.192 mg/kg bodyweight
cobalt sulphate (10124-43-3)	
LD50 oral rat	768 mg/kg
LD50 dermal rat	> 2000 mg/kg
ATE CLP (oral)	768.000 mg/kg bodyweight
nickel sulphate (7786-81-4)	
LD50 oral rat	361.9 mg/kg
LC50 inhalation rat (mg/l)	2.48 mg/l/4h
ATE CLP (oral)	361.900 mg/kg bodyweight
ATE CLP (vapours)	2.480 mg/l/4h
ATE CLP (dust,mist)	2.480 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : May cause cancer.

cobalt sulphate (10124-43-3)	
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
nickel sulphate (7786-81-4)	
NOAEL (chronic, oral, animal/male, 2 years)	11 mg/kg bodyweight
NOAEL (chronic, oral, animal/female, 2 years)	11 mg/kg bodyweight

Reproductive toxicity : May damage fertility or the unborn child.

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms

Symptoms/injuries after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause cancer by inhalation.

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

Likely routes of exposure : Inhalation;Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

Ecology - water : Very toxic to aquatic life with long lasting effects.

cobalt sulphate (10124-43-3)	
LOEC (chronic)	1.61 mg/l 23% survival
NOEC (chronic)	0.81 mg/l 28 days

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

nickel sulphate (7786-81-4)

LC50 fish 1	15.3 mg/l 96 h, no mortality observed
EC50 Daphnia 1	> 200 µg/l 48 h

12.2. Persistence and degradability

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

Persistence and degradability	May cause long-term adverse effects in the environment.
-------------------------------	---

12.3. Bioaccumulative potential

cobalt sulphate (10124-43-3)

Bioaccumulative potential	Not expected to bioaccumulate.
---------------------------	--------------------------------

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT and TDG

Transport document description	: UN3077 Environmentally hazardous substances, solid, n.o.s. (cobalt sulphate), 9, III
UN-No.(DOT)	: UN3077
Proper Shipping Name (DOT)	: Environmentally hazardous substances, solid, n.o.s. (cobalt sulphate)
Transport hazard class(es) (DOT)	: 9 - Class 9 (Miscellaneous dangerous materials)
Packing group (DOT)	: III - Minor Danger
Dangerous for the environment	: Yes
Marine pollutant	: Yes



ADR

Transport document description	: UN 3077 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (cobalt sulphate), 9, III, (E)
Proper Shipping Name (ADR)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (cobalt sulphate)
Packing group (ADR)	: III
Transport hazard class(es) (ADR)	: 9
Dangerous for the environment	: Yes
Marine pollutant	: Yes



Transport by sea

UN-No. (IMDG)	: UN 3077
Proper Shipping Name (IMDG)	: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (cobalt sulphate)
Transport hazard class(es) (IMDG)	: 9
Packing group (IMDG)	: III
Dangerous for the environment	: Yes

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Marine pollutant : Yes



Air transport

UN-No. (IATA) : UN 3077
Proper Shipping Name (IATA) : Environmentally hazardous substance, solid, n.o.s. (cobalt sulphate)
Transport hazard class(es) (IATA) : 9
Packing group (IATA) : III
Dangerous for the environment : Yes
Marine pollutant : Yes



SECTION 15: Regulatory information

15.1. US Federal regulations

cobalt sulphate (10124-43-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

nickel sulphate (7786-81-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Cobalt(II) sulphate (10124-43-3)

Listed on the Canadian DSL (Domestic Substances List) inventory

nickel sulphate (7786-81-4)

Listed on the Canadian DSL (Domestic Substances List) inventory

EU-Regulations

Cobalt(II) sulphate (10124-43-3)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

nickel sulphate (7786-81-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS)

All ingredients are listed in the Toxic Substances Control Act (TSCA)

All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL)

15.3. US State regulations

nickel sulphate (7786-81-4)

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New York - Right to Know List of Hazardous Chemicals

U.S. - Pennsylvania - List of Hazardous Substances

Thermomelt® HEAT-STIK Marker 750 °F (399, 400 °C), 800 °F (427 °C)


Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SECTION 16: Other information

- Data sources : ACGIH (American Conference of Government Industrial Hygienists).
European Chemicals Agency (ECHA) C&L Inventory database. Accessed at <http://echa.europa.eu/web/guest/information-on-chemicals/cl-inventory-database>.
Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition.
National Fire Protection Association. Fire Protection Guide to Hazardous Materials; 10th edition.
OSHA 29CFR 1910.1200 Hazard Communication Standard.
TSCA Chemical Substance Inventory. Accessed at <http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html>.
- Abbreviations and acronyms : ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number.
CLP: Classification, Labelling, Packaging.
EC50: Environmental Concentration associated with a response by 50% of the test population.
GHS: Globally Harmonized System (of Classification and Labeling of Chemicals).
LD50: Lethal Dose for 50% of the test population.
OSHA: Occupational Safety & Health Administration.
PBT: Persistent, Bioaccumulative, Toxic.
TWA: Time Weight Average.
TSCA: Toxic Substances Control Act.
- Other information : None.

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 1 - Must be preheated before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Full text of H-statements:

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product