

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

LA-CO Industries, Inc.

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 03/10/2015
Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Temperature indicator

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Acute Tox. 4 (Oral) H302
Skin Irrit. 2 H315
Eye Irrit. 2A H319
STOT SE 3 H335

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS07

Signal word (GHS-US) :

Warning

Hazard statements (GHS-US) :

H302 - Harmful if swallowed
H315 - Causes skin irritation
H319 - Causes serious eye irritation
H335 - May cause respiratory irritation

Precautionary statements (GHS-US) :

P261 - Avoid breathing dust, fume
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear eye protection, protective clothing, protective gloves
P301+P312 - If swallowed: Call a doctor if you feel unwell
P302+P352 - If on skin: Wash with plenty of water
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312 - Call a doctor if you feel unwell
P321 - Specific treatment (see First aid measures on this label)
P330 - Rinse mouth
P332+P313 - If skin irritation occurs: Get medical advice/attention
P337+P313 - If eye irritation persists: Get medical advice/attention
P362 - Take off contaminated clothing and wash before reuse
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

P501 - Dispose of contents/container to an approved waste disposal plant

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
3,5-dinitrobenzoic acid	(CAS No) 99-34-3	80	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 Aquatic Chronic 4, H413

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after inhalation : May cause respiratory irritation.
- Symptoms/injuries after skin contact : Causes skin irritation.
- Symptoms/injuries after eye contact : Causes serious eye irritation.
- Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No specific fire or explosion hazard.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear a self contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

- Protective equipment : Chemical goggles or safety glasses. protective gloves. In case of inadequate ventilation wear respiratory protection.

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Chemical goggles or safety glasses. Use neoprene or rubber gloves. Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Do not discharge into drains or the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain and collect as any solid. Avoid generating dust.

Methods for cleaning up : Take up in non-combustible absorbent material and shove into container for disposal. Minimize generation of dust.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid breathing dust, fume. Use only outdoors or in a well-ventilated area.

Hygiene measures : Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible products : Strong acids. Strong oxidizers. Strong bases.

7.3. Specific end use(s)

Temperature indicator.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)	
ACGIH	Not applicable
OSHA	Not applicable
3,5-dinitrobenzoic acid (99-34-3)	
ACGIH	Not applicable
OSHA	Not applicable

8.2. Exposure controls

Appropriate engineering controls : Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Either local exhaust or general room ventilation is usually required.

Hand protection : Wear suitable gloves. rubber.

Eye protection : Chemical goggles or safety glasses.

Skin and body protection : Wear suitable protective clothing. Impervious clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Use air-purifying respirator equipped with particulate filtering cartridges.

Thermal hazard protection : Flame retardant clothing should be used when handling in molten state.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Solid

Appearance : A solid crayon-like marker.

Colour : pale. Orange.

Odour : odourless.

Odour threshold : No data available

pH : No data available

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 198 °C / 388 °F
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: > 1
Solubility	: In water, material is partially soluble.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content : 0 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable at ambient temperature and under normal conditions of use.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Avoid creating or spreading dust. Contact with incompatible materials.

10.5. Incompatible materials

Strong oxidizing agents. Strong bases. Strong acids.

10.6. Hazardous decomposition products

Burning produces irritating, toxic and noxious fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed.

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

ATE CLP (oral)	2000.000 mg/kg bodyweight
----------------	---------------------------

3,5-dinitrobenzoic acid (99-34-3)

LD50 oral rat	1600 (1600 - 3200) mg/kg
ATE CLP (oral)	1600.000 mg/kg bodyweight

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated exposure) : Not classified

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Aspiration hazard	: Not classified
Potential adverse human health effects and symptoms	
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Swallowing a small quantity of this material will result in serious health hazard. Harmful if swallowed.
Likely routes of exposure	: Skin and eye contact;Inhalation

SECTION 12: Ecological information

12.1 Toxicity

3,5-dinitrobenzoic acid (99-34-3)	
LC50 fish 1	42.33 mg/l 96 h
EC50 Daphnia 1	1073.362 mg/l 48 h

12.2. Persistence and degradability

3,5-dinitrobenzoic acid (99-34-3)	
Biodegradation	50 % 38 d

12.3. Bioaccumulative potential

3,5-dinitrobenzoic acid (99-34-3)	
Log Pow	1.5098

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT and TDG

Not considered a dangerous good for transport regulations

Proper Shipping Name (ADR) : Not applicable

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

3,5-dinitrobenzoic acid (99-34-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

3,5-dinitrobenzoic acid (99-34-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	

EU-Regulations

3,5-dinitrobenzoic acid (99-34-3)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)	

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

National regulations

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).


All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

No additional information available

SECTION 16: Other information

Indication of changes	: Original Document.
Data sources	: ACGIH 2000. Canadian Centre for Occupational Health and Safety. Accessed at: http://www.ccohs.ca/oshanswers/legis/whmis_classifi.html . ESIS (European chemical Substances Information System; accessed at: http://esis.jrc.ec.europa.eu/index.php?PGM=cla . European Chemicals Agency (ECHA) Registered Substances list. Accessed at http://echa.europa.eu/ . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .
Abbreviations and acronyms	: ACGIH (American Conference of Government Industrial Hygienists). ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CLP: Classification, Labelling, Packaging. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. PBT: Persistent, Bioaccumulative, Toxic. STEL: Short Term Exposure Limits. TSCA: Toxic Substances Control Act. TWA: Time Weight Average.
Other information	: None.
NFPA health hazard	: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 4	Hazardous to the aquatic environment — Chronic Hazard, Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H413	May cause long lasting harmful effects to aquatic life

Thermomelt® HEAT-STIK Marker 388 °F (198, 200 °C)

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

SDS Prepared by: The Redstone Group, LLC
6397 Emerald Pkwy.
Suite 200
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product