

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)
Date of issue: 04/06/2015
Version: 1.0

LA-CO Industries, Inc.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F
Synonyms : Thermomelt® HEAT-STIK Markers : 113 °F (45 °C), 131 °F (55 °C), 138 °F (59 °C, 60 °C), 163 °F (73, 75 °C), 188 °F (87 °C), 194 °F (90 °C), 238 °F (114 °C), 256 °F (124, 125 °C), 269 °F (131, 132 °C), 319 °F (159, 160 °C), 325 °F (163 °C), 338 °F (170 °C), 344 °F (173 °C), 375 °F (191 °C), 425 °F (218 °C), 438 °F (225 °C), 525 °F (274, 275 °C), 600 °F (316 °C), 650 °F (343, 350 °C), 850 °F (450, 454 °C), 900 °F (482 °C), 932 °F (500 °C), 950 °F (510 °C), 1000 °F (538 °C), 1022 °F (550 °C), 1100 °F (593, 600 °C), 1200 °F (649, 650 °C), 1250 °F (677 °C), 1300 °F (700, 704 °C), 1350 °F (732 °C), 1400 °F (750, 760 °C), 1425 °F (774 °C), 1450 °F (788 °C), 1480 °F (800, 804 °C), 1500 °F (816 °C), 1550 °F (843, 850 °C), 1600 °F (871 °C), 1650 °F (899, 900 °C), 1700 °F (927 °C), 1900 °F (1038 °C), 1950 °F (1066 °C), 2000 °F (1100 °C), 2050 °F (1121 °C), 2200 °F (1200, 1204 °C)

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Temperature indicator

1.3. Details of the supplier of the safety data sheet

LA-CO Industries, Inc.
1201 Pratt Boulevard
Elk Grove Village, IL. 60007-5746
Phone: (847) 956-7600
Fax: (847) 956-9885
E-mail: customer_service@laco.com



1.4. Emergency telephone number

Emergency number : 24-hour emergency: CHEMTREC- U.S. : 1-800-424-9300 International: +1-703-527-3887

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification in accordance with the Globally Harmonized Standard

Not classified

2.2. Label elements

GHS-US labelling

No labelling applicable

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

3.2. Mixture

Name	Product identifier	% (w/w)	GHS-US classification
dilithium molybdate	(CAS No) 13568-40-6	5.46 : 850 °F 0 others	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified	(CAS No) 64742-95-6	1.37 : 600 °F 0 others	Asp. Tox. 1, H304 (benzene < 0.1%)
1,2,4-trimethylbenzene	(CAS No) 95-63-6	1.37 : 600 °F 0 others	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Aquatic Chronic 2, H411

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
- First-aid measures after skin contact : Wash skin with mild soap and water.
- First-aid measures after eye contact : If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.

4.3. Indication of any immediate medical attention and special treatment needed

All treatments should be based on observed signs and symptoms of distress in the patient.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Carbon dioxide. Dry powder. Foam. Water spray.
- Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : No specific fire or explosion hazard.
- Reactivity : No dangerous reactions known.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Do not allow run-off from fire fighting to enter drains or water courses.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Wear fire/flame resistant/retardant clothing. Wear a self contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Avoid contact with skin and eyes. Avoid creating or spreading dust.

6.1.1. For non-emergency personnel

- Protective equipment : In case of inadequate ventilation wear respiratory protection.
- Emergency procedures : Evacuate unnecessary personnel.

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

6.1.2. For emergency responders

Protective equipment : Where excessive vapour, mist, or dust may result, use approved respiratory protection equipment.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain and collect as any solid. Avoid generating dust.
Methods for cleaning up : Take up in non-combustible absorbent material and shove into container for disposal. Minimize generation of dust.

6.4. Reference to other sections

Section 13: disposal information. Section 7: safe handling. Section 8: personal protective equipment.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust, fume.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool well ventilated place. Keep container closed when not in use.
Incompatible products : Strong acids. Strong oxidizers. Strong bases.
Incompatible materials : Sources of ignition.

7.3. Specific end use(s)

Temperature indicator.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

dilithium molybdate (13568-40-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)		
ACGIH	Not applicable	
OSHA	Not applicable	
1,2,4-trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (mg/m ³)	123 mg/m ³
ACGIH	ACGIH TWA (ppm)	25 ppm
OSHA	Not applicable	
Canada (Quebec)	VECD (mg/m ³)	172 mg/m ³
Canada (Quebec)	VECD (ppm)	35 ppm
Canada (Quebec)	VEMP (mg/m ³)	123 mg/m ³
Canada (Quebec)	VEMP (ppm)	25 ppm

8.2. Exposure controls

Appropriate engineering controls : Avoid dispersal of dust in the air (ie, clearing dust surfaces with compressed air). Provide local exhaust ventilation of closed transfer systems to minimize exposures.

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Personal protective equipment	: Avoid all unnecessary exposure.
Hand protection	: It is a good industrial hygiene practice to minimize skin contact. If dust is formed: Wear dust impervious gloves
Eye protection	: In case of dust production: protective goggles.
Respiratory protection	: In case of inadequate ventilation wear respiratory protection. Use air-purifying respirator equipped with particulate filtering cartridges.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: A solid crayon-like marker.
Colour	: Various.
Odour	: odourless.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Various
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: > 1
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Avoid creating or spreading dust. Direct sunlight. Keep away from sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents. Strong bases. Strong acids.

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

10.6. Hazardous decomposition products

Carbon dioxide. Carbon monoxide. metallic oxides. Potassium oxides. Sulphur oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Not classified. Dermal: Not classified. Inhalation:dust,mist: Not classified.

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5610 mg/l/4h

1,2,4-trimethylbenzene (95-63-6)	
LD50 oral rat	3415 mg/kg
LD50 dermal rat	3440 mg/kg
LC50 inhalation rat (ppm)	954 ppm
ATE CLP (oral)	3415.000 mg/kg bodyweight
ATE CLP (dermal)	3440.000 mg/kg bodyweight
ATE CLP (dust,mist)	1.500 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified.

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential adverse human health effects and symptoms

Likely routes of exposure : Inhalation;Skin and eye contact

SECTION 12: Ecological information

12.1 Toxicity

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)	
LC50 fish 1	8.2 mg/l
EC50 Daphnia 1	4.5 mg/l
EC50 other aquatic organisms 1	3.7 mg/l
NOEC (acute)	0.5 mg/l

1,2,4-trimethylbenzene (95-63-6)	
LC50 fish 1	7.72 mg/l
LC50 other aquatic organisms 1	3.6 mg/l
EC50 other aquatic organisms 1	2.356 mg/l

12.2. Persistence and degradability

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)	
Persistence and degradability	Not established.

12.3. Bioaccumulative potential

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)	
Bioaccumulative potential	Not established.

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT and TDG
Not considered a dangerous good for transport regulations
Proper Shipping Name (ADR) : Not applicable

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

dilithium molybdate (13568-40-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

1,2,4-trimethylbenzene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

dilithium molybdate (13568-40-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

1,2,4-trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List) inventory.

EU-Regulations

dilithium molybdate (13568-40-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified (64742-95-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

1,2,4-trimethylbenzene (95-63-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

National regulations

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

All components are listed on the EEC inventory European Inventory of Existing Commercial Chemical Substances (EINECS).

All ingredients are listed in the Toxic Substances Control Act (TSCA).


All ingredients are listed on the Canadian Domestic Substances List (DSL) or Non-Domestic Substances List (NDSL).

15.3. US State regulations

No additional information available

16: Other information

Indication of changes	: Original Document.
Data sources	: ACGIH 2000. Canadian Centre for Occupational Health and Safety. Accessed at: http://www.ccohs.ca/oshanswers/legisl/whmis_classifi.html . ESIS (European chemical Substances Information System); accessed at: http://esis.jrc.ec.europa.eu/index.php?PGM=cla . European Chemicals Agency (ECHA) Registered Substances list. Accessed at http://echa.europa.eu/ . Krister Forsberg and S.Z. Mansdorf, "Quick Selection Guide to Chemical Protective Clothing", Fifth Edition. National Fire Protection Association; Fire Protection Guide to Hazardous Materials; 10th edition. OSHA 29CFR 1910.1200 Hazard Communication Standard. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006. TSCA Chemical Substance Inventory. Accessed at http://www.epa.gov/oppt/existingchemicals/pubs/tscainventory/howto.html .
Abbreviations and acronyms	: ACGIH (American Conference of Government Industrial Hygienists). ATE: Acute Toxicity Estimate. CAS (Chemical Abstracts Service) number. CLP: Classification, Labelling, Packaging. EC50: Environmental Concentration associated with a response by 50% of the test population. GHS: Globally Harmonized System (of Classification and Labeling of Chemicals). LD50: Lethal Dose for 50% of the test population. OSHA: Occupational Safety & Health Administration. PBT: Persistent, Bioaccumulative, Toxic. STEL: Short Term Exposure Limits. TSCA: Toxic Substances Control Act. TWA: Time Weight Average.
Other information	: None.
NFPA health hazard	: 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.
NFPA fire hazard	: 1 - Must be preheated before ignition can occur.
NFPA reactivity	: 0 - Normally stable, even under fire exposure conditions, and not reactive with water.



Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4

Thermomelt® HEAT-STIK Markers : 113 °F, 131 °F, 138 °F, 163 °F, 188 °F, 194 °F, 238 °F, 256 °F, 269 °F, 319 °F, 325 °F, 338 °F, 344 °F, 375 °F, 425 °F, 438 °F, 525 °F, 600 °F, 650 °F, 850 °F, 900 °F, 932 °F, 950 °F, 1000 °F, 1022 °F, 1100 °F, 1150 °F, 1200 °F, 1250 °F, 1300 °F, 1350 °F, 1400 °F, 1425 °F, 1450 °F, 1480 °F, 1500 °F, 1550 °F, 1600 °F, 1650 °F, 1700 °F, 1900 °F, 1950 °F, 2000 °F, 2050 °F, 2200 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
according to Canadian Hazardous Products Regulations (HPR)

Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation, Category 2A
Flam. Liq. 3	Flammable liquids, Category 3
Skin Irrit. 2	Skin corrosion/irritation, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H411	Toxic to aquatic life with long lasting effects

SDS Prepared by: The Redstone Group, LLC
6077 Frantz Rd.
Suite 206
Dublin, OH USA 43016
T 614-923-7472
www.redstonegrp.com

LACO NA GHS SDS

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product